Dust Control Plan Section 1 – General Information – Page 1

1-A Project Name a	and Location
Project Name:	
Project Address:	
	County:
	Township: Range:
Expected Construction	Start Date: End Date:
1-B Contacts	
preparation, submittal,	esses, and phone numbers of persons and owners or operators responsible for the and implementation of the Dust Control Plan and responsible for the dust dust control applications.
Property Owner:	
	Fax:
Developer:	
City / State / Zip: _	
Phone: _	Fax:
General Contractor:	
City / State / Zip: _	
Phone: _	Fax:
This Dust Control Plan	was prepared by:
Name: _	
Company Name: _	
Address:	
	Fax:
Date training completed	l: Training Location:

Section 1 – General Information – Page 2

Project Name:		
1-C	Contractors	
	de the names, addresses, and phone numbers of the contractors involved in dust generating activities forming dust control as part of this project.	
1		
2		
3.		
4		
5.		
-		
1-D Who will have the primary responsibility for implementing this Dust Control Plan?		
_	(Rule 8021 Sec 6.3.6.1)	
	Property Owner	
	Sub-Contractor(s) Other:	
Prim	nary Project Contact:	
	Title:	
Con	npany Name:	
	Address:	
City	/ State / Zip:	
	-Site Phone: Fax:	
	obile Phone: Pager:	
1-E	Provide a brief description of the Project's Operations.	
· ·		

Dust Control Plan Section 2 – Plot Plan – Page 1

Project Name:		
2-A Plot Plan		
A plot plan identifies the type and location of each project. project boundaries outlined or use the space in sections 2-B or may include tract maps, site maps, and topographic maps. Use have been identified on the plot plan.	r 2-C to draw a plot plan. Attached maps	
Identify the relative locations of actual and potential sources of fugitive dust emissions. Bulk material handling and storage areas. Paved and unpaved access roads, haul roads, traffic areas, and equipment storage yards. Exit points where carryout and trackout onto paved public roads may occur. Water supply locations if water application will be used for controlling visible dust emissions.		
Identify the relative locations of sensitive receptors within ½ ☐ No sensitive receptors within ¼ mile of the project. ☐ Residential areas, schools, day care, churches, hospitals, nursi ☐ Freeways, roads, or traffic areas that may be affected by the du ☐ Other:	ing facilities, commercial, retail, etc.	
2-B Draw Plot Plan (if one is not attached)	May use the back of this form Include a North Arrow	
☐ Plot plan is attached (Skip to 3-A).		

Section 2 – Plot Plan – Page 2

Proje	Project Name:		
2-C	Draw Plot Plan (if one is not attached)	Include a North Arrow	

Dust Control Plan Section 3 – Fugitive PM10 Sources – Page 1

Project Name:			
3-A Disturbed Surface Area			
Report the total area of land surface to be disturbed, yards, and the total area in acres of the entire project s			
Total area of land surfa	ce to be disturbed: Acres		
Daily maximum throughput volur	ne of earthmoving: Cubic Yards		
Daily average throughput volur	ne of earthmoving: Cubic Yards		
Total area of	entire project site: Acres		
Total disturbed areas that will be left inactive for more	e than seven days: Acres		
3-B Dust Generating Activity Dates			
The expected start and completion dates of dust generating activities and soil disturbance activities to be performed on site. For phased projects, it may be necessary to report expected start and completion dates separately.			
Expected start date:	Completion Date:		
Phase Project Start – A:	Completion – A:		
Phase Project Start – B:	Completion – B:		
Phase Project Start – C: Completion – C:			
3-C Other Locations			
Identify whether any other locations should be included example may include listing any site where materials w			
☐ No other locations are included with this project. (Skip to 3-D)			
Location 1:			
☐ No Dust Control Plan Required ☐ Included	with this plan 🔲 Included with another plan		
Location 2:			
☐ No Dust Control Plan Required ☐ Included	with this plan		
Location 3:			
☐ No Dust Control Plan Required ☐ Included	with this plan		

Section 3 – Fugitive PM10 Sources – Page 2

Project Name:	
3-D S	ources of Fugitive Dust
	tion describes the minimum requirements for limiting visible dust emissions from activities that gitive dust emissions. Check at least one box under each category.
Structu	ral Demolition.
	No demolitions are planned for this project.
	Asbestos NESHAP notification and fees have been submitted to the District.
	Water will be applied to the following areas for the duration of the demolition activities:
	Building exterior surfaces; Unpowed surface areas where againment will energies.
	 Unpaved surface areas where equipment will operate; Razed building materials; and
	 Water or dust suppressants will be applied to unpaved surface areas within 100 feet of structure during demolition.
Pre-Act	ivity.
	Not applicable for this project (Please explain why in Section 3-F).
	The site will be pre-watered and work will be phased to reduce the amount of disturbed surface area at any one time (Complete Section 4-A).
Active (Operations.
	Water will be applied to dry areas during leveling, grading, trenching, and earthmoving activities (Complete
	Section 4-A). Wind barriers will be constructed and maintained, and water or dust suppressants will be applied to the disturbed surface areas (Complete Sections 4-A or 4-B, and 4-C).
Inactive	Operations, including after work hours, weekends, and holidays.
	Not applicable for this project (Please explain why in Section 3-F).
	Water or dust suppressants will be applied on disturbed surface areas to form a visible crust, and vehicle access will be restricted to maintain the visible crust. (Complete Section 4-A or 4-B, and 4-C)
Tempor	ary stabilization of areas that remain unused for seven or more days.
	Not applicable for this project (Please explain why in Section 3-F)
	Vehicular access will be restricted and water or dust suppressants will be applied and maintained at all unvegetated areas (Complete Section 4-A or 4-B, and 4-C).
	Vegetation will be established on all previously disturbed areas (Complete Section 4-C).
	Gravel will be applied and maintained at all previously disturbed areas (Complete Section 4-C).
Ш	Previously disturbed areas will be paved (Complete Section 4-C).
Unpave	d Access and Haul Roads, Traffic and Equipment Storage Areas.
	Not applicable for this project (Please explain why in Section 3-F)
	Apply water or dust suppressants to unpaved haul and access roads (Complete Section 4-A or 4-B)
	Post speed limit signs of not more than 15 miles per hour at each entrance, and again every 500 feet. (Complete Section 4-C)
	Water or dust suppressants will be applied to vehicle traffic and equipment storage areas (Complete Section 4-A or 4-B).
Wind Events.	
	• Water application equipment will apply water to control fugitive dust during wind events, unless unsafe
	 to do so. Outdoor construction activities that disturb the soil will cease whenever visible dust emissions cannot be effectively controlled.

Section 3 – Fugitive PM10 Sources – Page 3

suppressants will be applied. Outdoor Storage of Bulk Materials. No bulk materials will be stored during this project. Water or dust suppressants will be applied to storage piles. Storage piles will be covered with tarps, plastic, or other suitable material and anchored in such a mann that prevents the cover from being removed by wind action. Wind barriers with less than 50 percent porosity will be installed and maintained around the storage pile and water or dust suppressants will be applied. A three-sided structure (< 50% porosity) will be used that is at least as high as the storage piles. On-Site Transporting of Bulk Materials. No bulk materials will be transported on the project site. Vehicle speed will be limited on the work site. All haul trucks will be loaded such that the freeboard is not less than six inches when transported acro any paved public access road. A sufficient amount of water will be applied to the top of the load to limit visible dust emissions. Haul trucks will be covered with a tarp or other suitable cover. Off-Site Transporting of Bulk Materials. No bulk materials will be transported to or from the project site. The following practices will be performed: (complete Section 5-B) The interior of emptied truck cargo compartments will be cleaned or covered before leaving the site. Spillage or loss of bulk materials from holes or other openings in the cargo compartment's floor, side and taligates will be prevented. Haul trucks will be covered with a tarp or other suitable cover or will be loaded such that the freeboa is not less than six inches when transported on any paved public access road to or from the proje site and a sufficient amount of water will be applied to the top of the load to limit visible due missions. Outdoor Transport using a Chute or Conveyor. No chutes or conveyors will be used. Chute or conveyor will be fully enclosed. Water spray equipment will be washed or screened to remove fines (PM10 or smaller).	3-E	Bulk Materials		
Water or dust suppressants will be applied when handling bulk materials. Wind barriers with less than 50 percent porosity will be installed and maintained, and water or dust suppressants will be applied. Outdoor Storage of Bulk Materials. No bulk materials will be stored during this project. Water or dust suppressants will be applied to storage piles. Storage piles will be covered with tarps, plastic, or other suitable material and anchored in such a mann that prevents the cover from being removed by wind action. Wind barriers with less than 50 percent porosity will be installed and maintained around the storage piles and water or dust suppressants will be applied. A three-sided structure (< 50% porosity) will be used that is at least as high as the storage piles. On-Site Transporting of Bulk Materials. No bulk materials will be transported on the project site. Vehicle speed will be limited on the work site. All haul trucks will be loaded such that the freeboard is not less than six inches when transported acro any paved public access road. A sufficient amount of water will be applied to the top of the load to limit visible dust emissions. Haul trucks will be covered with a tarp or other suitable cover. Off-Site Transporting of Bulk Materials. No bulk materials will be transported to or from the project site. The following practices will be performed: (complete Section 5-B) The interior of emptied truck cargo compartments will be cleaned or covered before leaving the site. Spillage or loss of bulk materials from holes or other openings in the cargo compartment's floor, side and tailgates will be prevented. Haul trucks will be prevented. Haul trucks will be covered with a tarp or other suitable cover or will be loaded such that the freeboar is not less than six inches when transported on any paved public access road to or from the project site and a sufficient amount of water will be applied to the top of the load to limit visible demissions. Outdoor Transport using a Chute or Conveyor. No	Outdo	Outdoor Handling of Bulk Materials.		
Outdoor Storage of Bulk Materials. No bulk materials will be stored during this project. Water or dust suppressants will be applied to storage piles. Storage piles will be covered with tarps, plastic, or other suitable material and anchored in such a mann that prevents the cover from being removed by wind action. Wind barriers with less than 50 percent porosity will be installed and maintained around the storage pile and water or dust suppressants will be applied. A three-sided structure (< 50% porosity) will be used that is at least as high as the storage piles. On-Site Transporting of Bulk Materials. No bulk materials will be transported on the project site. Vehicle speed will be limited on the work site. All haul trucks will be loaded such that the freeboard is not less than six inches when transported acro any paved public access road. A sufficient amount of water will be applied to the top of the load to limit visible dust emissions. Haul trucks will be covered with a tarp or other suitable cover. Off-Site Transporting of Bulk Materials. No bulk materials will be transported to or from the project site. The following practices will be performed: (complete Section 5-B) The interior of emptied truck cargo compartments will be cleaned or covered before leaving the site. Spillage or loss of bulk materials from holes or other openings in the cargo compartment's floor, side and taligates will be prevented. Haul trucks will be covered with a tarp or other suitable cover or will be loaded such that the freeboa is not less than six inches when transported on any paved public access road to or from the project site and a sufficient amount of water will be applied to the top of the load to limit visible due missions. Outdoor Transport using a Chute or Conveyor. No chutes or conveyors will be used. Chute or conveyor will be fully enclosed. Water spray equipment will be used to sufficiently wet the materials. Transported materials will be washed or screened to remove fines (PM10 or smaller).		Water or dust suppressants will be applied when handling bulk materials.Wind barriers with less than 50 percent porosity will be installed and maintained, and water or dust		
Water or dust suppressants will be applied to storage piles. Storage piles will be covered with tarps, plastic, or other suitable material and anchored in such a mann that prevents the cover from being removed by wind action. Wind barriers with less than 50 percent porosity will be installed and maintained around the storage pile and water or dust suppressants will be applied. A three-sided structure (< 50% porosity) will be used that is at least as high as the storage piles. On-Site Transporting of Bulk Materials. No bulk materials will be transported on the project site. Vehicle speed will be limited on the work site. All haul trucks will be loaded such that the freeboard is not less than six inches when transported acro any paved public access road. A sufficient amount of water will be applied to the top of the load to limit visible dust emissions. Haul trucks will be covered with a tarp or other suitable cover. Off-Site Transporting of Bulk Materials. No bulk materials will be transported to or from the project site. The following practices will be performed: (complete Section 5-8) The interior of emptied truck cargo compartments will be cleaned or covered before leaving the site. Spillage or loss of bulk materials from holes or other openings in the cargo compartment's floor, side and tailgates will be prevented. Haul trucks will be covered with a tarp or other suitable cover or will be loaded such that the freeboar is not less than six inches when transported on any paved public access road to or from the project site and a sufficient amount of water will be applied to the top of the load to limit visible demissions. Outdoor Transport using a Chute or Conveyor. No chutes or conveyors will be used. Chute or conveyor will be fully enclosed. Water spray equipment will be used to sufficiently wet the materials. Transported materials will be washed or screened to remove fines (PM10 or smaller).	Outdo			
 No bulk materials will be transported on the project site. □ Vehicle speed will be limited on the work site. □ All haul trucks will be loaded such that the freeboard is not less than six inches when transported acro any paved public access road. □ A sufficient amount of water will be applied to the top of the load to limit visible dust emissions. □ Haul trucks will be covered with a tarp or other suitable cover. Off-Site Transporting of Bulk Materials. □ No bulk materials will be transported to or from the project site. □ The following practices will be performed: (complete Section 5-B) • The interior of emptied truck cargo compartments will be cleaned or covered before leaving the site. • Spillage or loss of bulk materials from holes or other openings in the cargo compartment's floor, side and tailgates will be prevented. • Haul trucks will be covered with a tarp or other suitable cover or will be loaded such that the freeboar is not less than six inches when transported on any paved public access road to or from the project site and a sufficient amount of water will be applied to the top of the load to limit visible duemissions. Outdoor Transport using a Chute or Conveyor. □ No chutes or conveyors will be used. □ Chute or conveyor will be fully enclosed. □ Water spray equipment will be used to sufficiently wet the materials. □ Transported materials will be washed or screened to remove fines (PM10 or smaller). 		 Water or dust suppressants will be applied to storage piles. Storage piles will be covered with tarps, plastic, or other suitable material and anchored in such a manner that prevents the cover from being removed by wind action. Wind barriers with less than 50 percent porosity will be installed and maintained around the storage piles, and water or dust suppressants will be applied. 		
 Vehicle speed will be limited on the work site. All haul trucks will be loaded such that the freeboard is not less than six inches when transported acro any paved public access road. A sufficient amount of water will be applied to the top of the load to limit visible dust emissions. Haul trucks will be covered with a tarp or other suitable cover. Off-Site Transporting of Bulk Materials. No bulk materials will be transported to or from the project site. The following practices will be performed: (complete Section 5-B) The interior of emptied truck cargo compartments will be cleaned or covered before leaving the site. Spillage or loss of bulk materials from holes or other openings in the cargo compartment's floor, side and tailgates will be prevented. Haul trucks will be covered with a tarp or other suitable cover or will be loaded such that the freeboar is not less than six inches when transported on any paved public access road to or from the project site and a sufficient amount of water will be applied to the top of the load to limit visible duemissions. Outdoor Transport using a Chute or Conveyor. No chutes or conveyors will be used. Chute or conveyor will be fully enclosed. Water spray equipment will be used to sufficiently wet the materials. Transported materials will be washed or screened to remove fines (PM10 or smaller). 	On-Si	_		
Off-Site Transporting of Bulk Materials. No bulk materials will be transported to or from the project site. The following practices will be performed: (complete Section 5-B) The interior of emptied truck cargo compartments will be cleaned or covered before leaving the site. Spillage or loss of bulk materials from holes or other openings in the cargo compartment's floor, side and tailgates will be prevented. Haul trucks will be covered with a tarp or other suitable cover or will be loaded such that the freeboar is not less than six inches when transported on any paved public access road to or from the projective and a sufficient amount of water will be applied to the top of the load to limit visible due emissions. Outdoor Transport using a Chute or Conveyor. No chutes or conveyors will be used. Chute or conveyor will be fully enclosed. Water spray equipment will be used to sufficiently wet the materials. Transported materials will be washed or screened to remove fines (PM10 or smaller).		Vehicle speed will be limited on the work site. All haul trucks will be loaded such that the freeboard is not less than six inches when transported across any paved public access road. A sufficient amount of water will be applied to the top of the load to limit visible dust emissions.		
 No bulk materials will be transported to or from the project site. The following practices will be performed: (complete Section 5-B) The interior of emptied truck cargo compartments will be cleaned or covered before leaving the site. Spillage or loss of bulk materials from holes or other openings in the cargo compartment's floor, side and tailgates will be prevented. Haul trucks will be covered with a tarp or other suitable cover or will be loaded such that the freeboar is not less than six inches when transported on any paved public access road to or from the project site and a sufficient amount of water will be applied to the top of the load to limit visible duemissions. Outdoor Transport using a Chute or Conveyor. No chutes or conveyors will be used. Chute or conveyor will be fully enclosed. Water spray equipment will be used to sufficiently wet the materials. Transported materials will be washed or screened to remove fines (PM10 or smaller). 	Off-Si	·		
 No chutes or conveyors will be used. Chute or conveyor will be fully enclosed. Water spray equipment will be used to sufficiently wet the materials. Transported materials will be washed or screened to remove fines (PM10 or smaller). 		 No bulk materials will be transported to or from the project site. The following practices will be performed: (complete Section 5-B) The interior of emptied truck cargo compartments will be cleaned or covered before leaving the site. Spillage or loss of bulk materials from holes or other openings in the cargo compartment's floor, sides, and tailgates will be prevented. Haul trucks will be covered with a tarp or other suitable cover or will be loaded such that the freeboard is not less than six inches when transported on any paved public access road to or from the project site and a sufficient amount of water will be applied to the top of the load to limit visible dust emissions. 		
 Chute or conveyor will be fully enclosed. Water spray equipment will be used to sufficiently wet the materials. Transported materials will be washed or screened to remove fines (PM10 or smaller). 	Outdo			
 Water spray equipment will be used to sufficiently wet the materials. Transported materials will be washed or screened to remove fines (PM10 or smaller). 	L			
Transported materials will be washed or screened to remove fines (PM10 or smaller).				
3-F Comments		·····		
	3-F Comments			

Dust Control Plan Section 4 – Dust Control Methods – Page 1

Project Name:		
4-A Water Application		
Complete this section if water application will be used as a emissions and stabilizing surface areas. Check and answer ever		
Water Application Equipment:		
Sprinklers: Describe the activities that will utilize sprinklers:		
Minimum treated area:	_	
Maximum treated area:	_	
Minimum water flow rate: Duration:		
☐ Water Truck, ☐ Water Trailer, ☐ Water Wagon, ☐ Other:		
Describe the activities that will utilize this equipment:		
Number of application equipment available:		
Application and invariant association		
Application frequency:		
Application rate: Gallons per acr	e per application	
Hours of operation:		
Water application equipment is available to operate after normal working	ng hours, on weekends, and holidays.	
After-hours contact:	Phone No.:	
After-hours contact:	Phone No.:	
Water Supply: Include the relative leasting of these sources of	n the plat plan in Section 2	
Water Supply: Include the relative locations of these sources o	if the plot plan in Section 2.	
Fire hydrants	04.00	
Number of hydrants available On-Site:	Off-Site:	
Approval granted by the owner or public agency to use their fir	. ,	
	Dhara Na	
Contact:	Phone No.:	
_		
Canal, River, Pond, Lake, etc. Describe:	ntar aguras for this project	
Approval granted by the owner or public agency to use their wa		
	Dhana Na .	
Contact:	Phone No.:	
Other:		

Section 4 – Dust Control Methods – Page 2

Project Name:		
4-B Dust Suppress	ant Products	
Complete this section if a dust suppressant product will be used. These materials include, but are not limited to: hygroscopic suppressants (road salts), adhesives, petroleum emulsions, polymer emulsions, and bituminous materials (road oils). Copy this page if more than one dust suppressant product will be used.		
Not Applicable. O	nly water application will be the control method used. Skip to 4-C.	
Application Area:		
	Phone No:	
Application Rate:	Gallons of undiluted material per mile or acre treated.	
Application Frequency:	Applications per 🗌 week, 🗌 month, 🗌 year	
Application Equipment:		
Number of Application	Equipment Available:	
Application	Equipment Capacity:	
Attach each of the follow sure all information is su	ving information that fully describes this product. Use the checklist below to make bmitted with this plan.	
☐ Product Specifica	ations (MSDS, Product Safety Data Sheet, etc.)	
Manufacturer's U	sage Instructions (method, frequency, and intensity of application)	
Environmental im ground applicatio	npacts and approvals or certifications related to the appropriate and safe use for n.	

Section 4 – Dust Control Methods – Page 3

Project Name:		
4-C Other Dust Control Methods		
Check below the other types of dust control methods that will be employed at the construction site.		
 Physical barriers for restricting unauthorized vehicle access: ☐ Fences ☐ Gates ☐ Posts ☐ Berms ☐ Concrete Barriers ☐ Other: 		
☐ Wind barriers Describe:		
Posted speed limit signs meet State and Federal Department of Transportation standards.		
☐ Posted at 15 miles per hour, ☐ Posted at miles per hour (less than 15 MPH) ☐ Re-establish vegetation for temporarily stabilizing previously disturbed surfaces.		
Explain:		
Apply and maintain gravel: On haul roads On access roads At equipment storage yards At vehicle traffic areas For temporarily stabilizing previously disturbed areas.		
Explain:		
Apply pavement:		
Explain:		
4-D Contingencies		
Contingencies to be implemented if application equipment becomes inoperable, more equipment is needed to effectively control fugitive dust emissions during active and inactive periods, accessibility limitations occur at the water sources, or staff is not available to operate the application equipment. Describe the contingencies that will be in place and when they will be implemented. Attach any additional information if needed.		
4-E Record keeping (Rule 8011 Sec. 6.2)		
Records and any other supporting documents for demonstrating compliance must be maintained, but only for those days when a control measure is implemented. The District has developed record keeping forms that may be used for complying with this requirement. Check one or both below:		
Records will be maintained using the forms developed by the District.		
Records will be maintained using documents or forms developed by the owner or operator.		
Explain and include copies:		

Dust Control Plan Section 5 – Carryout and Trackout – Page 1

Project Name:
5-A Treatments for Preventing Trackout
Select the control devices that will be used for preventing trackout from occurring onto paved public roads. Trackout is any material that adheres to vehicle tires and is deposited onto a paved public road or the paved shoulder of a paved public road. Check one or a combination that will apply to this project.
Grizzly: Rails, pipes, or grates used to dislodge debris off of vehicles before exiting the site. Extends from the intersection with the paved public road surface for the full width of the unpaved exit surface for a distance of at least 25 feet.
Describe:
☐ Gravel Pad: A layer of washed gravel at least one (1) inch or larger in diameter, three (3) inches deep, and extends from the intersection with the public paved road surface for the full width of the unpaved exit surface for a distance of at least 50 feet.
Gravel Size: Inches
Pad Width: Feet Length: Feet Depth: Inches
Paved Surface: Extends from the intersection with the paved public road surface for the full width of the unpaved access road for at least 100 feet to allow mud and dirt to drop off of vehicles before exiting the site.
Width: Feet Length: Feet Mud and dirt deposits accumulating on paved interior roads will be removed with sufficient frequency, but not less frequently than once per workday. Cleanup will commence within ½ hour of generating any carryout and trackout.
Clean-up Frequency:
Wheel Washer: Uses water to dislodge debris from tires and vehicle undercarriage. (Rule 8011 Sec. 3.73)
Describe:
Other:
5-B Treatments for Preventing Carryout
Report the required treatments that will be used for preventing carryout from occurring on paved public roads. Carryout occurs when materials from emptied or loaded haul trucks, vehicles, or trailers falls onto a paved public road or paved shoulder of a paved public road.
 No haul trucks will be routinely entering or leaving the project site. Emptied Haul Trucks: □ Interior cargo compartments will be cleaned before leaving the project site.
Cargo compartment will be covered with a tarp or suitable cover before leaving the project site.
 Loaded Haul Trucks: Spillage or loss of materials from holes or other opening in the cargo compartment will be prevented when material is transported onto any paved public access road. (Rule 8031 Sec 5.0) Select one or both of the required applications: Haul trucks will be loaded such that the freeboard is not less than six inches with water applied to the top of
the load before leaving the project site. Cargo compartment and load will be covered with a tarp or suitable cover before leaving the project site.
Other:

Section 5 – Carryout and Trackout – Page 2

Project Name:		
5-C Cleaning up Carryout and Trackout		
Check and report below the methods and frequency for cleaning up carryout and trackout from the surface and paved shoulders of paved public roads.		
The use of blower devices, or dry rotary brushers or brooms, for removal of carryout and trackout from paved public roads is prohibited.		
In the event the control device becomes ineffective due to an accumulation of mud and dirt, material must be removed within $\frac{1}{2}$ hour of the generation of carryout and trackout.		
The project is located in:		
 An Urban Area, within an incorporated city boundary or an unincorporated area surrounded by a city. Minimum cleanup frequency will be at the end of the workday and removed immediately if carryout and trackout extends beyond 50 feet. A Rural Area, located within an unincorporated area and not surrounded by an incorporated city. 		
 The construction project is less than 10 acres in size: minimum cleanup frequency is at the end of the workday. Construction projects 10 or more acres in size: minimum cleanup frequency is end of the workday and immediately if carryout and trackout extends beyond 50 feet. 		
Clean up Method: Check the method below that will be used for cleaning carryout and trackout.		
Manually sweeping and picking up.		
Mechanical sweeping with a rotary brush or broom accompanied or preceded by water. Describe the types of equipment that will used:		
Operating a PM10-efficient street sweeper.		
Make and Model:		
 Flushing with water: allowed if: No curbs or gutters are present. Using water will not result as a source of trackout and carryout. Using water will not result in adverse impacts on storm water drainage systems. Using water will not violate any National Pollutant Discharge Elimination System permit program. 		
5-D Record keeping for Cleanup of Carryout and Trackout		
Records and any other supporting documents for demonstrating compliance must be maintained. The District has developed a record keeping form specific for cleaning carryout and trackout from paved public roads and may be used for complying with this requirement. Check one or both below:		
Records will be maintained using the form developed by the District.		
Records will be maintained using documents or forms developed by the owner or operator.		
Explain and include copies:		

Dust Control Plan Section 6 – Certification

Project Name:		
6-A Certification		
I certify that all information documents are true and compared to the compared		ormation submitted in the attachments to this
Print Name		
Print Name		Title
Signature		Date
Phone Number	Fax Number	Cell Number